

**Spallation Neutron Source  
Accumulator Ring and Transport  
Design Manual**

(DRAFT; July 2002)

## Preface

This document describes the design of the accumulator ring and the transport lines of the Spallation Neutron Source Project.

# Contents

<b>1</b>	<b>Overview</b>	<b>6</b>
1.1	Introduction . . . . .	7
1.2	Design Philosophy . . . . .	8
1.3	Performance Requirements . . . . .	9
1.4	Interface Requirements . . . . .	10
1.5	Coordinates and Polarity Conventions . . . . .	11
1.6	Acknowledgments . . . . .	12
<b>2</b>	<b>Accelerator Design and Beam-dynamics Issues</b>	<b>13</b>
2.1	Layout . . . . .	14
2.1.1	HEBT layout . . . . .	15
2.1.2	Ring layout . . . . .	16
2.1.3	RTBT layout . . . . .	17
2.2	Lattice . . . . .	18
2.2.1	Optics . . . . .	19
2.2.2	Working points and tuning . . . . .	20
2.2.3	Acceptance . . . . .	21
2.3	Beam Loss Mechanisms . . . . .	22
2.3.1	Controlled beam loss . . . . .	23
2.3.2	Uncontrolled beam loss . . . . .	24
2.4	Single-particle Effects . . . . .	25
2.4.1	Kinematic nonlinearity . . . . .	26
2.4.2	Magnet imperfection and nonlinearities . . . . .	27
2.4.3	Magnet fringe fields . . . . .	28
2.4.4	Chromatic effects . . . . .	29
2.4.5	Resonances and dynamic aperture . . . . .	30
2.5	Multi-particle Effects . . . . .	31
2.5.1	Space charge . . . . .	32
2.5.2	Coupling impedances . . . . .	33
2.5.3	Transverse instabilities . . . . .	34
2.5.4	Longitudinal instabilities . . . . .	35
2.5.5	Electron-cloud effects . . . . .	36
<b>3</b>	<b>Accelerator Physics and Technical Engineering</b>	<b>37</b>
3.1	Magnet System . . . . .	38
3.1.1	Magnet system requirements . . . . .	39
3.1.2	HEBT magnets . . . . .	40
3.1.3	Ring magnets . . . . .	41
3.1.4	RTBT magnets . . . . .	42
3.1.5	Magnet measurements and tests . . . . .	43
3.2	Magnet Power-supply System . . . . .	44
3.2.1	Power-supply requirements . . . . .	45

3.2.2	Power-supply layout . . . . .	46
3.2.3	HEBT magnet power supply . . . . .	47
3.2.4	Ring main-magnet power supply . . . . .	48
3.2.5	RTBT magnet power supply . . . . .	49
3.3	Correction System . . . . .	50
3.3.1	Closed-orbit correction . . . . .	51
3.3.2	Resonance correction . . . . .	52
3.4	Vacuum System . . . . .	52
3.4.1	Vacuum requirements . . . . .	53
3.4.2	Vacuum layout . . . . .	54
3.4.3	Vacuum chamber coating . . . . .	55
3.5	Injection . . . . .	56
3.5.1	Transverse phase-space painting . . . . .	57
3.5.2	Longitudinal phase-space painting . . . . .	58
3.5.3	H <sup>0</sup> and H <sup>-</sup> stripping control . . . . .	59
3.5.4	Stripped-electron collection . . . . .	60
3.5.5	Injection chicane perturbation . . . . .	61
3.5.6	Stripping foil assembly . . . . .	62
3.5.7	Injection magnets . . . . .	63
3.5.8	Ring injection-magnet power supply . . . . .	64
3.6	Extraction . . . . .	65
3.6.1	Extraction requirements . . . . .	66
3.6.2	Extraction layout . . . . .	67
3.6.3	Extraction magnets . . . . .	68
3.6.4	Extraction-magnet power supply . . . . .	69
3.6.5	Coupling-impedance measurements . . . . .	70
3.7	Beam Scraping and Collimation . . . . .	71
3.7.1	HEBT transverse collimation . . . . .	72
3.7.2	HEBT longitudinal collimation . . . . .	73
3.7.3	Ring transverse collimation . . . . .	74
3.7.4	Ring beam-in-gap cleaning . . . . .	75
3.7.5	RTBT transverse collimation . . . . .	76
3.7.6	Moveable scrapers design . . . . .	77
3.7.7	Collimator design . . . . .	78
3.8	Beam Dump . . . . .	79
3.8.1	Linac beam dump . . . . .	80
3.8.2	Injection beam dump . . . . .	81
3.8.3	Extraction beam dump . . . . .	82
3.9	Radio-frequency System . . . . .	83
3.9.1	RF system requirements . . . . .	84
3.9.2	HEBT RF system . . . . .	85
3.9.3	Ring RF system . . . . .	86
3.9.4	RF power supplies . . . . .	87
3.10	Diagnostics System . . . . .	88

3.10.1	Diagnostics requirements . . . . .	89
3.10.2	Diagnostics layout . . . . .	90
3.10.3	Beam position monitor . . . . .	91
3.10.4	Beam profile monitor . . . . .	92
3.10.5	Beam loss monitor . . . . .	93
3.10.6	Beam current monitor . . . . .	94
3.11	Survey and Installation . . . . .	95
3.11.1	Magnet survey . . . . .	96
3.11.2	Installation support . . . . .	97
<b>4</b>	<b>Controls and Protection</b>	<b>98</b>
4.1	Requirements . . . . .	99
4.2	Global Controls System . . . . .	100
4.2.1	Timing system . . . . .	101
4.2.2	machine protection . . . . .	102
4.3	Ring Controls System . . . . .	103
<b>5</b>	<b>Discussions and Options</b>	<b>104</b>
5.1	Operations at a Reduced Beam Energy . . . . .	105
5.2	Path to 1.3 GeV Operation . . . . .	106
5.3	Upgrades to a Higher Beam Power . . . . .	107
<b>6</b>	<b>Appendices</b>	<b>108</b>
6.1	Parameter Lists . . . . .	109
6.1.1	Primary parameters . . . . .	110
6.1.2	Magnet parameters . . . . .	111
6.1.3	Power-supply parameters . . . . .	112
6.1.4	RF system parameters . . . . .	113
6.2	Optics Files . . . . .	114
6.3	Index of Design Technical Notes . . . . .	115
6.4	Abbreviations and Acronyms . . . . .	116
6.5	List of Symbols . . . . .	117

# 1 Overview

## **1.1 Introduction**

## 1.2 Design Philosophy

## **1.3 Performance Requirements**

## 1.4 Interface Requirements

## 1.5 Coordinates and Polarity Conventions

## 1.6 Acknowledgments

Co-authors:

Acknowledgments:

Editor:

## **2 Accelerator Design and Beam-dynamics Issues**

## 2.1 Layout

### **2.1.1 HEBT layout**

### **2.1.2 Ring layout**

### **2.1.3 RTBT layout**

## 2.2 Lattice

### **2.2.1 Optics**

## **2.2.2 Working points and tuning**

### **2.2.3 Acceptance**

## **2.3 Beam Loss Mechanisms**

### **2.3.1 Controlled beam loss**

### **2.3.2 Uncontrolled beam loss**

## 2.4 Single-particle Effects

### **2.4.1 Kinematic nonlinearity**

## **2.4.2 Magnet imperfection and nonlinearities**

### **2.4.3 Magnet fringe fields**

#### **2.4.4 Chromatic effects**

### **2.4.5 Resonances and dynamic aperture**

## 2.5 Multi-particle Effects

### **2.5.1 Space charge**

## 2.5.2 Coupling impedances

### **2.5.3 Transverse instabilities**

## 2.5.4 Longitudinal instabilities

### **2.5.5 Electron-cloud effects**

### **3 Accelerator Physics and Technical Engineering**

## **3.1 Magnet System**

### **3.1.1 Magnet system requirements**

### 3.1.2 HEBT magnets

### **3.1.3 Ring magnets**

### **3.1.4 RTBT magnets**

### **3.1.5 Magnet measurements and tests**

## **3.2 Magnet Power-supply System**

### **3.2.1 Power-supply requirements**

### **3.2.2 Power-supply layout**

### **3.2.3 HEBT magnet power supply**

### **3.2.4 Ring main-magnet power supply**

### **3.2.5 RTBT magnet power supply**

### **3.3 Correction System**

### **3.3.1 Closed-orbit correction**

### **3.3.2 Resonance correction**

## **3.4 Vacuum System**

### **3.4.1 Vacuum requirements**

### **3.4.2 Vacuum layout**

### **3.4.3 Vacuum chamber coating**

## **3.5 Injection**

### **3.5.1 Transverse phase-space painting**

### **3.5.2 Longitudinal phase-space painting**

### 3.5.3 H<sup>0</sup> and H<sup>-</sup> stripping control

### **3.5.4 Stripped-electron collection**

### **3.5.5 Injection chicane perturbation**

### **3.5.6 Stripping foil assembly**

### **3.5.7 Injection magnets**

### **3.5.8 Ring injection-magnet power supply**

## **3.6 Extraction**

### **3.6.1 Extraction requirements**

### **3.6.2 Extraction layout**

### **3.6.3 Extraction magnets**

### **3.6.4 Extraction-magnet power supply**

### **3.6.5 Coupling-impedance measurements**

### **3.7 Beam Scraping and Collimation**

### **3.7.1 HEBT transverse collimation**

### **3.7.2 HEBT longitudinal collimation**

### **3.7.3 Ring transverse collimation**

### **3.7.4 Ring beam-in-gap cleaning**

### **3.7.5 RTBT transverse collimation**

### **3.7.6 Moveable scrapers design**

### **3.7.7 Collimator design**

## **3.8 Beam Dump**

### **3.8.1 Linac beam dump**

### **3.8.2 Injection beam dump**

### **3.8.3 Extraction beam dump**

### **3.9 Radio-frequency System**

### **3.9.1 RF system requirements**

### 3.9.2 HEBT RF system

### **3.9.3 Ring RF system**

### **3.9.4 RF power supplies**

### **3.10 Diagnostics System**

### **3.10.1 Diagnostics requirements**

### **3.10.2 Diagnostics layout**

### **3.10.3 Beam position monitor**

### **3.10.4 Beam profile monitor**

### **3.10.5 Beam loss monitor**

### **3.10.6 Beam current monitor**

### **3.11 Survey and Installation**

### **3.11.1 Magnet survey**

### **3.11.2 Installation support**

## 4 Controls and Protection

## 4.1 Requirements

## 4.2 Global Controls System

#### 4.2.1 Timing system

## 4.2.2 machine protection

## 4.3 Ring Controls System

## 5 Discussions and Options

## **5.1 Operations at a Reduced Beam Energy**

## **5.2 Path to 1.3 GeV Operation**

### **5.3 Upgrades to a Higher Beam Power**

## **6 Appendices**

## 6.1 Parameter Lists

### **6.1.1 Primary parameters**

### **6.1.2 Magnet parameters**

### **6.1.3 Power-supply parameters**

#### **6.1.4 RF system parameters**

## 6.2 Optics Files

### **6.3 Index of Design Technical Notes**

## **6.4 Abbreviations and Acronyms**

## **6.5 List of Symbols**

## References

- [1] *Spallation Neutron Source Design Manual*, June 1998.
- [2] *Preliminary Change Request for the SNS Ring Hybrid Lattice*, SNS/BNL Technical Note 66, edited by J. Wei, October 1999.